



US010280044B2

(12) **United States Patent**
Eastman et al.

(10) **Patent No.:** **US 10,280,044 B2**
(45) **Date of Patent:** **May 7, 2019**

(54) **IN-SERVICE REPAIR OF ELEVATOR BELT**

(71) Applicant: **Otis Elevator Company**, Farmington, CT (US)

(72) Inventors: **Scott Alan Eastman**, Glastonbury, CT (US); **John P. Wesson**, West Hartford, CT (US); **Daniel A. Mosher**, Glastonbury, CT (US); **Wenping Zhao**, Glastonbury, CT (US); **William Eaton Holden, III**, Berlin, CT (US); **Michael Paul Humbert**, Meriden, CT (US); **Brad Guilani**, Woodstock Valley, CT (US); **Gopal R. Krishnan**, Wethersfield, CT (US)

(73) Assignee: **OTIS ELEVATOR COMPANY**, Farmington, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 136 days.

(21) Appl. No.: **15/264,791**

(22) Filed: **Sep. 14, 2016**

(65) **Prior Publication Data**
US 2017/0073195 A1 Mar. 16, 2017

Related U.S. Application Data

(60) Provisional application No. 62/218,191, filed on Sep. 14, 2015.

(51) **Int. Cl.**
B66B 19/00 (2006.01)
B66B 7/06 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B66B 19/007** (2013.01); **B29C 73/02** (2013.01); **B29C 73/34** (2013.01); **B66B 7/062** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B66B 19/007; B66B 7/062; B66B 7/12; B66B 9/00; B29C 73/02; B29C 73/34
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,211,743 A * 7/1980 Nauta B29C 51/22 264/284
4,224,601 A * 9/1980 Davidson G01D 15/06 347/161

(Continued)

FOREIGN PATENT DOCUMENTS

CN 201872353 U 6/2011
JP H08133650 A 5/1996
WO 2015076827 A1 5/2015

OTHER PUBLICATIONS

Database WPI Week 201158, Thomson Scientific, London, GB, AN 2011-J47111, XP002765842, 2 pages.
European Search Report for application EP 16188708.8, dated Jan. 23, 2017, U320659EP, 10 pages.

Primary Examiner — Michael A Riegelman
(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57) **ABSTRACT**

A servicing device for a belt of an elevator system is provided including a housing and a guide member coupled to the housing. The guide member and the housing are disposed on opposite sides of the belt. At least one reservoir is disposed within the housing. The at least one reservoir contains one or more restoring materials. An applicator is configured to apply the one or more restoring materials to an adjacent surface of the belt. Application of the one or more restoring materials is configured to modify the geometry of the belt such that the modified geometry is substantially identical to the original geometry of the belt.

9 Claims, 9 Drawing Sheets

