

(12) **United States Patent**
Koba et al.

(10) **Patent No.:** **US 10,150,646 B2**
(45) **Date of Patent:** **Dec. 11, 2018**

- (54) **ELEVATOR DEVICE INCLUDING EVACUATION OPERATION MODE REQUEST SWITCH**
- (71) Applicant: **MITSUBISHI ELECTRIC CORPORATION**, Chiyoda-ku (JP)
- (72) Inventors: **Yoshimasa Koba**, Tokyo (JP); **Shinichi Kuroda**, Tokyo (JP); **Takaharu Ueda**, Veenendaal (NL); **Ashiqur Rahman**, Veenendaal (NL); **David Willem Lodewijk Offerhaus**, Veenendaal (NL)
- (73) Assignee: **MITSUBISHI ELECTRIC CORPORATION**, Chiyoda-ku (JP)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 380 days.

- (21) Appl. No.: **15/022,312**
- (22) PCT Filed: **Sep. 17, 2013**
- (86) PCT No.: **PCT/JP2013/075020**
§ 371 (c)(1),
(2) Date: **Mar. 16, 2016**
- (87) PCT Pub. No.: **WO2015/040669**
PCT Pub. Date: **Mar. 26, 2015**

(65) **Prior Publication Data**
US 2016/0280510 A1 Sep. 29, 2016

- (51) **Int. Cl.**
B66B 1/20 (2006.01)
B66B 5/02 (2006.01)
- (52) **U.S. Cl.**
CPC **B66B 5/021** (2013.01)
- (58) **Field of Classification Search**
CPC B66B 5/021

(Continued)

- (56) **References Cited**
U.S. PATENT DOCUMENTS
- 4,482,032 A * 11/1984 Enriquez B66B 1/468
187/392
- 5,086,450 A * 2/1992 Kitagawa H04M 11/04
187/390
- (Continued)

- FOREIGN PATENT DOCUMENTS
- EP 1 930 279 A1 6/2008
- JP 2003-276964 A 10/2003
- (Continued)

- OTHER PUBLICATIONS
- International Preliminary Report on Patentability and Written Opinion dated Mar. 31, 2016 in PCT/JP2013/075020 filed Sep. 17, 2013 (submitting English translation only).
- (Continued)

Primary Examiner — Anthony Salata
(74) *Attorney, Agent, or Firm* — Oblon, McClelland, Maier & Neustadt, L.L.P.

- (57) **ABSTRACT**
- An elevator device enabling efficient evacuation of people left in a building is provided. The elevator device includes: an evacuation operation mode request switch provided in a hall of an elevator on a rescue floor; a car that if the evacuation operation mode request switch is kept in an operated state, keeps operating in an evacuation operation mode in which the car moves between the rescue floor and an evacuation floor; and an operation control device that is provided in the hall of the elevator on the rescue floor, and if the operation control device is operated when the car is stopped at the rescue floor, moves the car to the evacuation floor.

9 Claims, 10 Drawing Sheets

