



US010189681B2

(12) **United States Patent**
Burri et al.

(10) **Patent No.:** **US 10,189,681 B2**
(45) **Date of Patent:** **Jan. 29, 2019**

(54) **ESCALATOR OR MOVING WALKWAY WITH AT LEAST ONE ACCESS MODULE**

USPC 198/321, 326
See application file for complete search history.

(71) Applicant: **INVENTIO AG**, Hergiswil (CH)

(56) **References Cited**

(72) Inventors: **Jürg Burri**, Hirschthal (CH); **Michael Matheisl**, Vösendorf (AT)

U.S. PATENT DOCUMENTS

(73) Assignee: **INVENTIO AG**, Hergiswil (CH)

4,674,619 A * 6/1987 Nakazawa B66B 23/02
198/331
5,348,131 A * 9/1994 Yamaguchi B66B 23/02
198/321

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/747,540**

CN 201587789 U 9/2010
CN 201 952 093 8/2011
CN 204022238 U 12/2014
EP 1 777 192 B1 3/2010
GB 2 205 803 12/1988

(22) PCT Filed: **Jul. 15, 2016**

(Continued)

(86) PCT No.: **PCT/EP2016/066959**

§ 371 (c)(1),
(2) Date: **Jan. 25, 2018**

OTHER PUBLICATIONS

(87) PCT Pub. No.: **WO2017/016905**

International Search Report for International Application No. PCT/EP2016/066959 dated Oct. 20, 2016.

PCT Pub. Date: **Feb. 2, 2017**

Primary Examiner — James R Bidwell

(65) **Prior Publication Data**

US 2018/0215589 A1 Aug. 2, 2018

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(30) **Foreign Application Priority Data**

Jul. 28, 2015 (EP) 15178552

(57) **ABSTRACT**

(51) **Int. Cl.**
B66B 23/00 (2006.01)
B66B 21/04 (2006.01)
B66B 21/10 (2006.01)

An escalator or moving walkway comprises two access areas. The escalator or the moving walkway comprises components generating thermal losses that are arranged in at least one of the access areas in a component room. The escalator or the moving walkway comprises at least one walkable access module, which is arranged adjacent to the component compartment. The access module comprises a cavity, wherein at least one opening exists between the component compartment and the cavity, through which the thermal energy of the components generating thermal losses can be transferred from the component compartment to the cavity.

(52) **U.S. Cl.**
CPC **B66B 23/00** (2013.01); **B66B 21/04** (2013.01); **B66B 21/10** (2013.01)

(58) **Field of Classification Search**
CPC B66B 21/02; B66B 21/00; B66B 23/00; B66B 23/026

19 Claims, 2 Drawing Sheets

