

(12) **United States Patent**
Aitamurto et al.

(10) **Patent No.:** **US 10,549,950 B2**
(45) **Date of Patent:** **Feb. 4, 2020**

(54) **METHOD AND AN ARRANGEMENT FOR ENABLING MOVEMENT OF THE ELEVATOR WHILE A MAINTENANCE TECHNICIAN IS IN THE PIT**

(71) Applicant: **KONE Corporation**, Helsinki (FI)
(72) Inventors: **Juha-Matti Aitamurto**, Hyvinkää (FI); **Pekka Laukkanen**, Hyvinkää (FI); **Ari Kattainen**, Hyvinkää (FI)
(73) Assignee: **KONE CORPORATION**, Helsinki (FI)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 481 days.

(21) Appl. No.: **15/387,383**
(22) Filed: **Dec. 21, 2016**
(65) **Prior Publication Data**
US 2017/0174474 A1 Jun. 22, 2017

(30) **Foreign Application Priority Data**
Dec. 22, 2015 (EP) 15201824

(51) **Int. Cl.**
B66B 1/34 (2006.01)
B66B 5/00 (2006.01)
B66B 1/02 (2006.01)

(52) **U.S. Cl.**
CPC **B66B 5/0087** (2013.01); **B66B 1/02** (2013.01); **B66B 5/005** (2013.01)

(58) **Field of Classification Search**
CPC B66B 5/0087; B66B 1/02; B66B 5/005; B66B 5/0056
USPC 187/247, 391, 393, 394, 293, 298
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,721,403 A *	2/1998	Hoppie	B66B 5/0087
				187/247
6,550,585 B2 *	4/2003	Schoppa	B66B 5/005
				187/280
7,448,473 B2 *	11/2008	Lindberg	B66B 1/34
				187/384
7,575,102 B2 *	8/2009	Matsuoka	B66B 5/0093
				187/391
7,891,467 B2 *	2/2011	Kattainen	B66B 5/0056
				187/316
7,954,606 B2 *	6/2011	Tinone	B66B 5/005
				187/384

(Continued)

FOREIGN PATENT DOCUMENTS

EP	2 072 450 A1	6/2009
EP	2 623 452 A1	8/2013
WO	WO 2013/061355 A1	5/2013

Primary Examiner — Anthony J Salata
(74) *Attorney, Agent, or Firm* — Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

The method of performing maintenance of an elevator is performed by unlocking and opening a landing door at a lowermost landing manually, activating a first stop button in the shaft, whereby a safety circuit of the elevator is opened so that operation of the car is completely prevented, entering into the shaft, closing the landing door, climbing down from the lowermost landing to the pit, turning a drive switch in a maintenance control unit positioned in the pit into a maintenance drive mode, whereby the first stop button is bypassed so that the car can be driven from the maintenance control unit upwards and downwards in the shaft.

2 Claims, 3 Drawing Sheets

