

(12) **United States Patent**
Studer et al.

(10) **Patent No.:** **US 10,549,951 B2**
(45) **Date of Patent:** **Feb. 4, 2020**

(54) **UNLOCKING DEVICE, ELEVATOR SYSTEM HAVING AN UNLOCKING DEVICE, AND METHOD FOR ACTUATING AN UNLOCKING DEVICE**

(71) Applicant: **Inventio AG**, Hergiswil (CH)

(72) Inventors: **Christian Studer**, Kriens (CH);
Raphael Bitzi, Lucerne (CH)

(73) Assignee: **INVENTIO AG**, Hergiswil NW (CH)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 295 days.

(21) Appl. No.: **15/533,729**

(22) PCT Filed: **Dec. 7, 2015**

(86) PCT No.: **PCT/EP2015/078769**

§ 371 (c)(1),

(2) Date: **Jun. 7, 2017**

(87) PCT Pub. No.: **WO2016/091777**

PCT Pub. Date: **Jun. 16, 2016**

(65) **Prior Publication Data**

US 2017/0320704 A1 Nov. 9, 2017

(30) **Foreign Application Priority Data**

Dec. 11, 2014 (EP) 14197474

(51) **Int. Cl.**

B66B 5/00 (2006.01)

B66B 9/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **B66B 5/0087** (2013.01); **B66B 9/00** (2013.01); **B66B 11/0246** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC B66B 5/0087; B66B 5/0043; B66B 9/00;
B66B 11/0246; B66B 13/22; B66B 13/24;
E05B 47/0002; E05B 65/006
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,727,657 A * 3/1998 Foelix B66B 5/005
187/356
6,138,798 A * 10/2000 Macuga B66B 5/005
187/294

(Continued)

FOREIGN PATENT DOCUMENTS

GB 1498039 A 1/1978
WO 2011076531 A1 6/2011

Primary Examiner — Michael A Riegelman

(74) *Attorney, Agent, or Firm* — William J. Clemens;
Shumaker, Loop & Kendrick, LLP

(57) **ABSTRACT**

An unlocking device with an actuator releases a safety cover of a maintenance opening for opening. The locking device has a safety circuit for actuating the actuator. The safety circuit includes at least one first switching contact and a second switching contact arranged in series, wherein the actuator in a closed state of the first and the second switching contacts is connected by the safety circuit with a power source, and the first switching contact can be switched by a control unit. One or more of the unlocking device can be used in an elevator system.

16 Claims, 3 Drawing Sheets

