



US010787341B2

(12) **United States Patent**
Herkel et al.

(10) **Patent No.:** **US 10,787,341 B2**
(45) **Date of Patent:** **Sep. 29, 2020**

(54) **ELEVATOR CONTROL SYSTEM AND ELEVATOR SYSTEM HAVING INSPECTION CONTROL STATION**

(58) **Field of Classification Search**
CPC ... B66B 5/0087; B66B 5/0025; B66B 5/0037; B66B 5/0062; B66B 1/3407; B66B 1/3461; B66B 9/00

(71) Applicants: **Otis Elevator Company**, Farmington, CT (US); **Peter Herkel**, Berlin (DE)

(Continued)

(72) Inventors: **Peter Herkel**, Berlin (DE); **Michael Mann**, Berlin (DE); **Helmut Lothar Schroeder-Brumloop**, Berlin (DE); **Pascal Rebillard**, Gien (FR); **Igor Kuzmin**, St. Petersburg (RU)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,203,506 A 8/1965 Cummins
5,554,832 A 9/1996 Lumme et al.
(Continued)

(73) Assignee: **OTIS ELEVATOR COMPANY**, Farmington, CT (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 272 days.

EP 1148018 A1 10/2001
EP 2072444 A1 6/2009
(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **15/740,674**

International Search Report and Written Opinion for application PCT/EP2015/064946, dated Mar. 22, 2016, 12 pages.

(22) PCT Filed: **Jul. 1, 2015**

(86) PCT No.: **PCT/EP2015/064946**

Primary Examiner — Christopher Uhler

§ 371 (c)(1),

(2) Date: **Dec. 28, 2017**

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(87) PCT Pub. No.: **WO2017/001005**

PCT Pub. Date: **Jan. 5, 2017**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2018/0186602 A1 Jul. 5, 2018

Elevator control system, comprising an elevator control device for operating an elevator car which is adapted to be operated within an elevator shaft, and an inspection control station configured to communicate with the elevator control device for operating at least one function of an elevator system in an inspection or maintenance operation mode, and configured for attachment at a storing location, wherein the storing location is at the elevator car or within the elevator shaft or in proximity of the elevator shaft. The inspection control station is adapted to be detachable from the storing location and configured to operate as remote inspection control station when detached from the storing location through wireless communication with the elevator control device, and is configured to be movable and operable in the

(51) **Int. Cl.**

B66B 5/00 (2006.01)

B66B 1/34 (2006.01)

B66B 9/00 (2006.01)

(52) **U.S. Cl.**

CPC **B66B 5/0087** (2013.01); **B66B 1/3407** (2013.01); **B66B 1/3461** (2013.01); **B66B 9/00** (2013.01); **B66B 2201/00** (2013.01)

(Continued)

